



LEER, INC. - CARROLL, IA 51401
 WOOD RAIL PANELS BUILDING UNITS (L61)
 UL 1715 - WALL-CILING CONSTRUCTION
 UL 723 - SURFACE BURN CHARACTERISTICS
 FLOOR BLOWING AGENT: HD 12322(6)
 9" THICK MAXIMUM FINISHED ALUMINUM STEEL
 PAINTED OR UNPAINTED
 CORE MATERIAL: 20 25 15 350
 FLAME BREED: 30 400 400
 SMOKE DEVELOPED: 140-300

NOTICE: CONCRETE AND TILE WORKERS
 *THE SHEET METAL FACING INSIDE THIS WALK-IN MAY STAIN OR OXIDIZE DUE TO EXCESSIVE MOISTURE CREATED BY HYDRATION OF CONCRETE MATERIALS.
 *EXTRA CARE MUST BE TAKEN WHEN USING MURIATIC ACID OR OTHER HARSH CLEANING MATERIALS.
 *EXTREMELY IMPORTANT TO VENTILATE THE WALK-IN PROPERLY WHILE CONCRETE IS CURING.

WARNING!
 ENGINEERED FOR ON-CEILING INSTALLATION. IF ANY FINISH OR A.C. OF THIS WALK-IN IS TO BE INSTALLED IN A DEPRESSION, CONTACT THE LEER, INC. SALES DEPT. IMMEDIATELY AT 1-800-764-8834

IMPORTANT!
 THIS WALK-IN IS DESIGNED TO SUPPORT ONLY ITS OWN WEIGHT. STORAGE ON TOP, MOUNTING TO, OR MODIFYING THE WALK-IN MAY VOID ALL MANUFACTURER'S WARRANTIES. ANY OUTDOOR WALK-IN MUST BE RESISTIVE TO WEATHERING, LOCAL SNOW LOAD AND LIVE LOAD REQUIREMENTS.

IMPORTANT!
 LEER, INC. MUST KNOW IF YOU ARE USING QUARRY WALK-IN. IF YOU ARE PUTTING UP TO THE WALK-IN, ROUGH OPENINGS FOR PASS THRU DOORS AND LEER, INC. DOORS WILL NEED MODIFICATION TO ALLOW THE DOORS TO OPEN AND CLOSE PROPERLY.

LEGEND

(1) WALL PANELS	T	THERMOMETER
(C1) CEILING PANELS	\$	LIGHT SWITCH
(F1) FLOOR PANELS	☐	VAPOR PROOF LIGHT
(H1) HEADERS	▨	SILLS
(HS1) HEADER SUPPORTS	▩	HEADERS w/70 SILLS
(S1) SILLS	⊗	CUTOFF OPENING
(R1) RETRO RAILS	▧	PLYWOOD
(RPT) EXTERIOR RAMPS	▨	URETHANE INSULATION
	☐	WALL BELOW OR ABOVE
	○	DETAIL

COMBO SPECIFICATIONS

- CHECKED: _____
- ACCESSORIES:
- (2) VAPOR PROOF LIGHT 115V (BULB NOT INCLUDED) - SHIPS LOOSE
 - (2) LIGHT SWITCH AND DIGITAL THERMOMETER 115V - SHIPS LOOSE
 - (1) HEATED VENT - 115V
 - (1) DOOR DRIP CAP - SHIPS LOOSE
 - (1) COVE MOLDING FOR BASE OF EXTERIOR

COMBO SPECIFICATIONS

- CHECKED: _____
- SIZE: 14'-0" x 6'-0" x 8'-0"
 - COOLER PANEL THICKNESS: 4" WALLS, & 4" CEILING
 - FREEZER PANEL THICKNESS: 5 1/2" WALLS, & 5 1/2" CEILING
 - FLOOR PANEL THICKNESS: 4 5/8"
 - EXTERIOR FINISH: (01) 26 GA. STUCCO GALVANIZED
 - INTERIOR FINISH: (01) 26 GA. STUCCO GALVANIZED
 - INTERIOR FLOOR FINISH: (21) 0.050 ALUMINUM
 - CEILING TYPE: LAG DOWN
 - FLOOR TYPE: STANDARD FLOOR WITH WOOD SCREED
 - DOOR DESCRIPTION: 1 QTY 34" x 76 1/4" OVERLAP SELF-CLOSING DOOR 4-SIDED GASKET
 - DOOR DESCRIPTION: 1 QTY 34" x 76 1/4" OVERLAP SELF-CLOSING DOOR 3-SIDED GASKET, 3-SIDED HTD FRAME, HTD THRESHOLD & HTD DOOR P

PANELS ARE WOOD FRAME CONSTRUCTION.
 THIS PANEL STYLE MAY NOT BE SUITABLE FOR A CLASS 1 OR CLASS 2 BUILDING CONSTRUCTION.
 WALK-IN COMPLIES WITH ALL PROVISIONS OF SECTION 312 OF THE ENERGY INDEPENDENCE AND SECURITY ACT OF 2007

CHAPTER 26 COMPLIANCE SUCH AS: A THERMAL BARRIER AS SPECIFIED IN IBC SECTION 2603.4 IS NOT REQUIRED BASED ON IBC SECTION 2603.5 SPECIAL APPROVAL IN ACCORDANCE WITH UL1715 TESTING.

2021 IBC C403.11 COMPLIANT

